

## **White Static Cling Film - TAG Digital®**

### **TECHNICAL DATA SHEET**

#### **Description:**

The **White Static Cling Film - TAG Digital®** is a white electrostatic soft PVC film without adhesive. It can be applied on windows and flat surfaces such as refrigerators, tiles, furniture, etc.

#### **Characteristics:**

The **White Static Cling Film - TAG Digital®** has a thickness of 180 microns which allows an easy application. The liner is a 170 gr/m<sup>2</sup> paper with double PE coating.

#### **Printing:**

The film can be printed with solvent, eco-solvent and UV inks.

#### **Use of the product:**

The presence of solvent components in the inks can soften the film and make it stretchable, therefore we recommend respecting a drying time of about 24 hours before lamination or placement. Without proper drying, solvent vapors can cause application difficulties and impair the adhesion to the substrate.

#### **Notes:**

Do not bring into contact with products containing solvents or ammonia. Thoroughly clean the substrate before application. Check before production that the product is compatible with the surface. Application temperature: 10° to 70° C.

#### **Placement:**

Clean the glass thoroughly. Apply on dry surface.

#### **Durability:**

The maximum recommended duration of use is 1 year.

#### **Storage:**

1 year between 15 and 25°C and a humidity of 45 to 55% in the original box.

**Product references:**

<b>White Static Cling Film 180<math>\mu</math></b>	<b>1,37 x 50 m</b>	STATW-PVC-180-137050
--	--------------------	----------------------

**Note:**

The information in this data sheet is based on laboratory tests and experience gained in practice. It does not constitute a legal guarantee. A test prior to use must be carried out.

Durability is estimated based on exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. Outdoor performance degradation can be expected when the films are exposed southward, if applied in areas with high temperatures such as Southern European countries, or in polluted areas.